



**STYLE: 7BPP**      **DATE: 11/11/16**

TEST METHOD	PROPERTY	SPECIFICATION
N/A	<b>CONSTRUCTION</b>	100% ecofi® Dura Lock® Technology Foss Solution Dyed Polyester Nonwoven Material (Heat Activated / Structured)
FTM NW508 (ASTM D3776)	<b>TOTAL WEIGHT</b>	17.0 oz/yd <sup>2</sup> +/-1.7 oz/yd <sup>2</sup>
FTM NW502 (ASTM D3774)	<b>WIDTH</b>	As Requested +0.5 in /-0 in
FTM NW504 (ASTM D5729)	<b>TOTAL THICKNESS</b>	0.210 in +/-0.020 in
FTM NW523	<b>PILE HEIGHT</b>	3.5 mm +/-0.5 mm
FTM NW505 (ASTM D5034)	<b>TENSILE STRENGTH</b>	MD     110 lbs min CMD    110 lbs min
FTM NW 506 (ASTM D5034)	<b>ELONGATION (Instron @ 25 lbs)</b>	MD     10% max CMD    10% max
VISUAL	<b>COLOR</b>	Match Approved Standard
VISUAL	<b>APPEARANCE</b>	Match Approved Standard

**REVISIONS**

DATE	DESCRIPTION	BY
11/11/16	First Issue: Tentative	T.N.