



STYLE: 7HD9

DATE: 11/18/19

TEST METHOD	PROPERTY	SPECIFICATION
N/A	CONSTRUCTION	100% ecofi® Dura-Lock® Technology Foss Solution Dyed Polyester Stryctured Nonwoven Material Single Rib (Made from 100% post-consumer plastic bottles)
FTM NW508 (ASTM D3776)	TOTAL WEIGHT	26.0 oz/yd ² +/-2.6 oz/yd ²
FTM NW504 (ASTM D5729)	TOTAL THICKNESS	0.250 in +/-0.025 in
PILE FTM NW523	PILE HEIGHT	3.0 mm +/- 0.5 mm
PILL TEST DOC (FF 1-70)	FLAMMABILITY	PASS
RADIANT PANEL (ASTM E648-14a)	CRITICAL RADIANT FLUX	NFPA 101 Classification: Class 1
SMOKE DENSITY (ASTM E662-13d)	OPTICAL SMOKE DENSITY	PASS
VISUAL	COLOR	Match Approved Standard
VISUAL	APPEARANCE	Match Approved Standard

REVISIONS

DATE	DESCRIPTION	BY
8/9/15	First Issue	T.N.
4/11/16	Rev 1: added flammability	T.N.
11/18/19	Rev 2: Added details	LTH