



STYLE: 7WD9

DATE: 4/11/16

TEST METHOD	PROPERTY	SPECIFICATION
N/A	CONSTRUCTION	100% ecofi [®] Dura-Lock [®] Technology Foss Solution Dyed Polyester Structured Nonwoven Material Wide Wale Cord (Made from 100% post-consumer plastic bottles)
FTM NW508 (ASTM D3776)	TOTAL WEIGHT	28.5 oz/yd ² +/-2,8 oz/yd ²
FTM NW504 (ASTM D5729)	TOTAL THICKNESS	0.300 in +/-0.030 in
PILE (FTM NW523)	PILE HEIGHT	5.0 mm +/-0.5 mm
PILL TEST DOC (FF 1-70)	FLAMMABILITY	PASS
RADIANT PANEL (ASTM E648-14a)	CRITICAL RADIANT FLUX	NFPA 101 Classification: Class 1
SMOKE DENSITY (ASTM E662-13d)	OPTICAL SMOKE DENSITY	PASS
VISUAL	COLOR	Variety of Colors Available
VISUAL	APPEARANCE	Structured Surface Pattern

REVISIONS

DATE	DESCRIPTION	BY
7/18/15	First Issue	T.N.
4/11/16	Rev 1: Added flammability tests	T.N.

243 Huffaker Rd NW • Rome, GA 30165
phone: 855-800-4060 • www.fossfloors.com